



PRODUCT DATA SHEET



VNIR E



SWIR 640

Micro-Hyperspec[®] Imaging Sensors

- Up to 369 spectral bands*
- Up to 1,600 spatial bands*
- Collect full hyperspectral data for every pixel
- Frame rates up to 450 Hz*

** depending on model chosen*

- VNIR, NIR, Ext. VNIR, SWIR versions
- Airborne and ground-based applications
- All-reflective, concentric optical layout
- High spectral & spatial resolution

PRODUCT DATA SHEET



Spectral Range	VNIR (400-1000nm)		NIR (900-1700nm)		Extended VNIR (600-1700nm)	SWIR (900-2500nm)	
Micro-Hyperspec® Configuration	A-Series*	E-Series	640	320	640	384*	640
Focal Plane Array	Silicon CCD	sCMOS	InGaAs			MCT	
Pixel Pitch (microns)	7.4	6.5	15	30	15	24	15
Aperture	F/2.5						
Slit Length (mm)	10.5						
Dispersion/Pixel (nm)	1.9	1.63	6	12	4.1	9.6	6
Entrance Slit Width (µm)	20		25		20	25	20
FWHM Slit Image (nm)	5.8	5.8	10	10	5.5	10	8
Spectral Bands	324	369	134	67	267	166	267
Spatial Bands	1004	1600	640	320	640	384	640
Aberration-Corrected	Yes						
Max. Frame Rate (Hz)	90	250	120	346	120	450	>200
ADC Bit Depth	12	16	14			16	
Cooling	No	TE-cooled	TE-cooled			Stirling-cooled	
Digital Output Format	Base CameraLink	Full CameraLink	Base CameraLink			RS232/Base CameraLink	Base CameraLink
Weight without lens (lb / kg)	1.6 / 0.7	2.4/1.1	1.9 / 0.9			4.4 / 2.0	3.4 / 1.6
Max Power (W)	6.6	20	5	5	5	16.8	24

* Call for availability.

APPLICATIONS



GEOLOGY & MINING



INFRASTRUCTURE INSPECTION



ENVIRONMENTAL

MAY 2021

© 2021 Headwall Photonics, Inc. Information in this document is subject to change without notice. Headwall Photonics, Inc. reserves the right to change or improve its products and specifications and to make changes in content without obligation to notify any person or organization of such changes or improvements. The Hyperspec® name (and all its derivations) is a registered Trademark of Headwall Photonics, Inc. *US and/or EU Export Restrictions may apply to this Dual Use Product.

contact information

Headwall Photonics, Inc.
580 Main Street • Bolton, Massachusetts 01740
978-353-4100
information@headwallphotonics.com